

WT15

Ultra-compact theatre enclosure

features

- Ultra-compact trapezoid enclosure
- ICT™ technology
- Vertical or horizontal orientation
- High SPL capability

applications



- Background music for clubs and bars
- Theatre delay/in-fill
- AV presentations



The ultra-compact WT15 is a trapezoid full-range speaker capable of producing SPL's associated with much larger enclosures. It is designed specifically for theatre applications where minimum size is a priority.

Only 11" high, it produces extended bandwidth and has high output capability from twin 5" (125mm) drivers assembled in an innovative two-way configuration utilising ICT™ technology. To maximise output, the 5" (125mm) loudspeaker is augmented by a second 5" (125mm) driver operating in tandem over the bass and mid-range region. HF dispersion is identical in both horizontal and vertical planes.

overall dimensions



WT15

technical specifications

TYPE	Ultra-compact, two-way ICT™ trapezoid
FREQUENCY RESPONSE (5)	120Hz-20kHz ± 3dB
DRIVERS	5" (125mm) bass driver 5" (125mm) ICT™ driver
RATED POWER (2)	75W AES, 300W peak
RECOMMENDED AMPLIFIER	50-100W into 4 ohms
SENSITIVITY (6)	91dB
MAXIMUM SPL (7)	108dB continuous, 114dB peak
NOMINAL IMPEDANCE	Externally switchable 4 or 16 ohms
DISPERSION (-6dB)	80° horizontal, 80° vertical
ENCLOSURE	5 litre, rear vented
FINISH	Textured black paint
PROTECTIVE GRILLE	Black perforated steel
CONNECTORS	2 x Neutrik NL4 switchable for input +1,-1 or +2,-2
FITTINGS	2 x 3/8" flush mounted nut plates on base and top 2 x M4 inserts for Omnimount 50
DIMENSIONS	(W) 172mm x (H) 282mm x (D) 172mm (W) 6.8ins x (H) 11ins x (D) 6.8ins
WEIGHT	5kg (11lbs)

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HP12 3SL, England.
Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2006 Martin Audio Ltd.



www.martin-audio.com